

PRODUCT SPECIFICATION SHEET

Item Name : Affinity

Specifications :

- Contents: Top - 100% PVC with proprietary top coating
Back – 100% polyester
- Width: 54”
- Nominal thickness: .044 gauge
- Nominal weight : 30oz/linear yard
- Repeat: N/A
- Roll Length: App. 30yds

General Characteristics :

- Authentic leather touch
- Superior wear resistance: Exceeds 100,000 rubs (ASTM D4157 Wyzenbeek)
- Anti-bacterial/Anti-microbial (AATCC-147)
- -20 degree F cold crack resistant (Fed. Standard 191A)
- Colorfastness to light (AATCC-16/passes 400 hours)
- Colorfastness to chlorine bleach (AATCC-3)
passes 1:10 & 1:5 bleach dilution
- Mildew Resistant (ASTM G21/AATCC 6275)
- Oil Resistant (AATCC 130-2000)

Flammability* :

- FMVSS-302
- CA Bulletin 117 – Class A
- UFAC/NFPA-260 Class 1
- BIFMA – Class A
- Port Authority of New York/New Jersey
- Boston Fire Dept. Code IX-1
- IMO A.652(16) 8.2 & 8.3
- ASTM E-84 (Adhered) Class A

*This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Care & Cleaning :

- Stain Removal: Spot clean with mild soap and warm water solution. Rinse the cleaned area with clean/clear water and dry with air or lint-free cloth

Disinfectability :

- Affinity is formulated to achieve a superior level of disinfectability with a 10:1 bleach solution.

Warranty : Please refer to our Terms of Sales for warranty information.